

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.08.2016

Version number 2

Revision: 04.08.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Castdon Color Monomer**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Mixing liquid for Castdon Color and - Intense Powder
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dreve Dentamid GmbH
Max-Planck-Straße 31
59423 Unna / Germany
Tel.: ++49 2303 / 8807-0
Fax.: ++49 2303 / 8807-55
- **Further information obtainable from:**
Department Research & Development
Fax: ++49 2303 / 8807-562
Email: sicherheitsdatenblatt@dreve.de
- **1.4 Emergency telephone number:**
Tel.: ++ 49 211 / 797-3350
Plant Fire Department Henkel

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
methyl methacrylate
- **Hazard statements**
H225 Highly flammable liquid and vapour.

(Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.08.2016

Version number 2

Revision: 04.08.2016

Trade name: Castdon Color Monomer

(Contd. of page 1)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:** Liquid based on methacrylate acid ester, containing an activator

- **Dangerous components:**

| | | |
|-------------------|--|---------|
| CAS: 80-62-6 | methyl methacrylate | 50-100% |
| EINECS: 201-297-1 | Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 | |

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:**

Do not induce vomiting.

Call a doctor immediately.

- **4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Irritant to skin and eyes

Sensitization possible through skin contact

- **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

GB

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.08.2016

Version number 2

Revision: 04.08.2016

Trade name: Castdon Color Monomer

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
 - Water
 - Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
 - In case of fire, the following can be released:
 - Carbon monoxide and carbon dioxide
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
 - Cool endangered receptacles with water spray.
 - Collect contaminated fire fighting water separately. It must not enter the sewage system.
 - Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Avoid contact with skin and eyes.
 - Ensure adequate ventilation
 - Wear protective clothing.
 - Keep away from ignition sources.
 - Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
 - Do not allow to penetrate the ground/soil.
 - Prevent seepage into sewage system, workpits and cellars.
 - Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - Send for recovery or disposal in suitable receptacles.
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Avoid contact with skin and eyes.
 - Keep away from heat and direct sunlight.
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.

(Contd. on page 4)

GB



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.08.2016

Version number 2

Revision: 04.08.2016

Trade name: **Castdon Color Monomer**

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Protect from heat and direct sunlight.
Store in a cool location.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

| | |
|--|--|
| Ingredients with limit values that require monitoring at the workplace: | |
| 80-62-6 methyl methacrylate | |
| WEL | Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm |

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- **Respiratory protection:**

Short term filter device:
Filter A.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

Protective gloves should be changed regularly, especially after intensive contact with the product. For every workplace a suitable type of protective gloves must be selected.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

Butyl rubber (0,7 mm) EN 374

As there are many different conditions in every day work these indications can only serve as an aid to orientation for the selection of suitable gloves for the handling of chemical products. By no means they can replace qualifying examinations by the end-user.

These recommendations only apply to the product mentioned in the safety data sheet. When mixing with other substances or under conditions deviant from norm EN 374 a manufacturer of CE-approved gloves should be referred to.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.08.2016

Version number 2

Revision: 04.08.2016

Trade name: Castdon Color Monomer

(Contd. of page 4)

therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:**

Solvent resistant protective clothing
Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Fluid
Colour: Colourless

- **Odour:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: -48 °C

Boiling point/Boiling range: 101 °C

- **Flash point:** 10 °C

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 430 °C

- **Decomposition temperature:** Not determined.

- **Self-igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower: 2.1 Vol %

Upper: 12.5 Vol %

- **Oxidising properties** Not determined

- **Vapour pressure at 20 °C:** 47 hPa

- **Density at 20 °C:** 0.967 g/cm³

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

(Contd. on page 6)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.08.2016

Version number 2

Revision: 04.08.2016

Trade name: **Castdon Color Monomer**

(Contd. of page 5)

| | |
|---|--|
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 0.0 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No dangerous reactions if used according to specifications.
- **10.2 Chemical stability** Stable if used according to specifications.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
Protect from heat and direct sunlight.
- **10.3 Possibility of hazardous reactions** Danger of polymerisation.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
Reacts with peroxides and other radical forming substances.
Reacts with reducing agents.
Reacts with heavy metals.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
Methylmethacrylate: LD-50 oral >5000 mg/kg rat (Lit.)
LD-50 inhalativ 7093 ppm/4h rat (Lit.)
- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 7)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.08.2016

Version number 2

Revision: 04.08.2016

Trade name: **Castdon Color Monomer**

(Contd. of page 6)

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
 - Fish Toxicity (MMA):
 - LC-50 > 79 mg/l OECD 203
 - NOEC: 40 mg/l ISO 7346
 - Exposure: 96 h EEC84
 - Spezies: 449 V, C1
 - Oncorhynchus mykiss
 - Bacterial Toxicity: ECO: 100 mg/l
 - Spezies of cells: Pseudomonas putida
- **12.2 Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Components:**
 - Methylmethacrylat:
 - Biodegradability: 30,7 %
 - Test Duration: 28 d
 - Method: OECD 301 C
 - Scoring: Not ready degradability
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 - Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 - Disposal must be made according to official regulations.
- **Waste disposal key:** 070104
- **European waste catalogue**

| | |
|-----------|--|
| 07 01 04* | other organic solvents, washing liquids and mother liquors |
|-----------|--|
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1247

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 04.08.2016

Version number 2

Revision: 04.08.2016

Trade name: **Castdon Color Monomer**

(Contd. of page 7)

| | |
|--|---|
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA | 1247 METHYLMETHACRYLAT, MONOMER, STABILISIERT, Lösung METHYL METHACRYLATE MONOMER, STABILIZED, solution |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA | |
|  <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids. 3 |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | II |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | No |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: | Warning: Flammable liquids. 339 F-E,S-D |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| <ul style="list-style-type: none"> · Transport/Additional information: | |
| <ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) | 1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| <ul style="list-style-type: none"> · Transport category · Tunnel restriction code | 2 D/E |
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| <ul style="list-style-type: none"> · UN "Model Regulation": | UN1247, METHYL METHACRYLATE MONOMER, STABILIZED solution, 3, II |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

(Contd. on page 9)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.08.2016

Version number 2

Revision: 04.08.2016

Trade name: Castdon Color Monomer

(Contd. of page 8)

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Information about limitation of use:**
Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
- **Department issuing SDS:** Department Research & Development
- **Contact:** Dr. Thomas Veit, Lothar Sutor, Susanne Langesberg
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB