

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.07.2015

Version number 2

Revision: 15.07.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: MegaBase Adhesive**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Priming
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dreve Dentamid GmbH
Max-Planck-Straße 31
59423 Unna / Germany
Tel.: ++49 2303 / 8807-0
Fax.: ++49 2303 / 8807-55
- **Further information obtainable from:**
Department Research & Development
Fax: ++49 2303 / 8807-562
Email: sicherheitsdatenblatt@dreve.de
- **1.4 Emergency telephone number:**
Tel.: ++ 49 211 / 797-3350
Plant Fire Department Henkel

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
ethyl acetate
methyl methacrylate

(Contd. on page 2)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.07.2015

Version number 2

Revision: 15.07.2015

Trade name: MegaBase Adhesive

(Contd. of page 1)

- **Hazard statements**
 - H225 Highly flammable liquid and vapour.
 - H319 Causes serious eye irritation.
 - H317 May cause an allergic skin reaction.
 - H336 May cause drowsiness or dizziness.
- **Precautionary statements**
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P405 Store locked up.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 141-78-6	ethyl acetate	50-100%
EINECS: 205-500-4	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 80-62-6	methyl methacrylate	2.5-10%
EINECS: 201-297-1	⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
 - Supply fresh air and to be sure call for a doctor.
 - In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
 - Immediately wash with water and soap and rinse thoroughly.
 - If skin irritation continues, consult a doctor.
- **After eye contact:**
 - Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
 - Try not to vomit. Swallow activated carbon and sodium sulphate.
 - Call a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
 - Nausea
 - Disziness
 - Headache

(Contd. on page 3)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.07.2015

Version number 2

Revision: 15.07.2015

Trade name: MegaBase Adhesive

(Contd. of page 2)

Vomitus

- **4.3 Indication of any immediate medical attention and special treatment needed**
If swallowed or in case of vomiting, danger of entering the lungs.
If swallowed, gastric irrigation.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Avoid contact with skin and eyes.
Ensure adequate ventilation
Do not breathe vapour/spray.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Avoid contact with skin and eyes.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Protect from heat and direct sunlight.
Store at max. 25 °C.
Store in a cool location.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 4)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.07.2015

Version number 2

Revision: 15.07.2015

Trade name: MegaBase Adhesive

(Contd. of page 3)

- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate

WEL	Short-term value: 400 ppm Long-term value: 200 ppm
-----	---

80-62-6 methyl methacrylate

WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
-----	--

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
Short term filter device:
Filter A.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

Protective gloves should be changed regularly, especially after intensive contact with the product. For every workplace a suitable type of protective gloves must be selected. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Material of gloves**

Butyl rubber (0,7 mm) EN 374

As there are many different conditions in every day work these indications can only serve as an aid to orientation for the selection of suitable gloves for the handling of chemical products. By no means they can replace qualifying examinations by the end-user.

These recommendations only apply to the product mentioned in the safety data sheet. When mixing with other substances or under conditions deviant from norm EN 374 a manufacturer of CE-approved gloves should be referred to.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.07.2015

Version number 2

Revision: 15.07.2015

Trade name: MegaBase Adhesive

(Contd. of page 4)

- **Penetration time of glove material**

Penetration time: > 120 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined.

- pH-value: Not determined.

- **Change in condition**

Melting point/Melting range:	-90.5 °C
Boiling point/Boiling range:	76 °C

- Flash point: -4 °C

- Flammability (solid, gaseous): Not applicable.

- Ignition temperature: 460 °C

- Decomposition temperature: Not determined.

- Self-igniting: Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower:	2.1 Vol %
Upper:	11.5 Vol %

- Oxidising properties: Not determined

- Vapour pressure at 20 °C: 97 hPa

· Density at 20 °C:	0.90 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

- Solubility in / Miscibility with water at 20 °C: 0.05 g/l

(Contd. on page 6)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.07.2015

Version number 2

Revision: 15.07.2015

Trade name: MegaBase Adhesive

(Contd. of page 5)

- | | |
|---|--|
| <ul style="list-style-type: none"> · Partition coefficient (n-octanol/water): Not determined. | |
| <ul style="list-style-type: none"> · Viscosity: <ul style="list-style-type: none"> Dynamic: Not determined. Kinematic: Not determined. | |
| <ul style="list-style-type: none"> · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No dangerous reactions if used according to specifications.
- **10.2 Chemical stability** Stable if used according to specifications.
- **Thermal decomposition / conditions to be avoided:**
Protect from heat and direct sunlight.
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Develops readily flammable gases/fumes.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** Sensitisation possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 7)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.07.2015

Version number 2

Revision: 15.07.2015


Trade name: **MegaBase Adhesive**

(Contd. of page 6)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA 	UN1173
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA 	1173 ETHYLACETAT, GEMISCH ETHYL ACETATE, MIXTURE
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA 	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	II
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: 	Warning: Flammable liquids. 33 F-E,S-E
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul style="list-style-type: none"> · Transport category · Tunnel restriction code 	2 D/E
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml

(Contd. on page 8)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.07.2015

Version number 2

Revision: 15.07.2015

Trade name: MegaBase Adhesive

(Contd. of page 7)

	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1173, ETHYL ACETATE, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations:**
- **Information about limitation of use:**
Employment restrictions concerning juveniles must be observed.
- **Technical instructions (air):**

Class	Share in %
NK	50-100
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
- **Department issuing MSDS:** Department Research & Development
- **Contact:** Dr. Thomas Veit, Lothar Sutor
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3